


Input Voltage	Output voltage	Output current	Output Power	Efficiency	Dimension
10-23V	24V	1A	24W	96.5%	74*32*18mm



The RW-968-12-24V-24W is a Non-isolated DC/DC boost converter that uses a synchronous rectification technology, and features high efficiency and power density. It has the dimensions of 64mm x 57mm x 22mm (2.52 in. x 2.24 in. x 0.86 in) and provides the rated output voltage of 24 V and the maximum output current of 1A.

Features

- Design meeting RoHS / CE
- High efficiency: 96.5%(@ 12Vin, 25°C)
- Non-isolated between input and output
- Mount in almost any location, high reliability
- Support -40 °C environment
- 100% full load burn-in test
- 3 month warranty
- Over load, Low voltage protections
- Waterproof level IP67
- Die-cast aluminum shell, epoxy potting

Applications

- Industrial
- Alternative Energy
- Golf Cart
- Forklift
- Electromotor
- Telecommunications
- Boat & Yacht
- Medical
- LED Marketplaces and so on

Model naming method

RW-968-12-24V-24W

RW-968 : SKU NAME
12: Input voltage range
24V: Output voltage
24W: POWER

Datasheet

Parameter	Min	Typ	Max	Units	Remarks
Absolute maximum ratings					
Operating ambient temperature	-40	-	+50	°C	
Shell ambient temperature	-40	-	80	°C	
Storage temperature	-55	-	100	°C	
Operating humidity	5	-	95	%	Non-condensing
Atmospheric pressure	62	-	106	kpa	
Altitude	-	-	4000	m	
Cooling way	-	-	-		Natural cooling
Input characteristics					
Input voltage	10	12	23	V	
Max. input voltage	-	-	23	V	Continuous
Undervoltage shutdown	8.0	8.2	8.5	V	Automatic recovery
Undervoltage recovery	9.6	9.8	10.0	V	Automatic recovery
Max. input current	-	-	2.8	A	Vin =9V; Iout =1A
No load current	-	20	30	mA	Vin =12V
Positive electrode cable	22	-	-	AWG	If the wire length is greater than 50cm, it is recommended to use a thicker wire diameter.
Negative electrode cable	22	-	-	AWG	

Enable PIN cable	-	NA	-	AWG	If the unit with this function
Fuse	-	20	-	A	Input positive has built-in fuse
Output characteristics					
Efficiency	-	96.5	-	%	Vin =12V; Iout =1A
Output voltage	23.8	24.2	24.5	V	Vin =12V; Iout =1A
Regulator accuracy	-	±3	-	%	
Voltage regulation	-	±2	-	%	
Load Regulation	-	±2	-	%	
Overvoltage protection	-	NA	-	V	
Output current	0	-	1	A	
Overcurrent protection	3.8	4.2	4.6	A	Vin=12V
External capacitance	-	NA	-	μF	Don't need
Output ripple and noise	-	260	300	mVp-p	Vin =10-23V; Iout=1A, Oscilloscope bandwidth: 20 MHz
Output voltage risetime	-	13	20	mS	
Boot delay time	-	20	30	mS	
Out voltage overshoot	-	-	5	%	Vin =12V, 50%-75%Load step
Over temperatur protection	-	NA	-	°C	Shell test

Short circuit protection	-	YES	-		Output can't shorted for boost converters
Positive electrode cable	22	-	-	AWG	If the wire length is greater than 50cm, it is recommended to use a thicker wire diameter
Negative electrode cable	22	-	-	AWG	
Safety and EMC features					
Anti-electric Strength	Input to Output	-		V	Leakage current \leq 3.5mA, 1min, no breakdown, no arcing
	Input to Shell	≥ 500		V	
	Output to Shell	≥ 500		V	
Insulation resistance	Input to Output				Test voltage = 500V
	Input to Shell	≥ 10		M Ω	
	Output to Shell				
Other characteristics					
Weight	≤ 80			g	
Package	white box				
MTBF	$\geq 200,000$			H	Vin= 12V; Iout= 1A
Switching frequency	130 \pm 10			KHz	

Characteristic Curves

Conditions: $T_A = 25^\circ\text{C}(77^\circ\text{F})$, $V_{in} = 12\text{ V}$, $V_{out} = 24\text{ V}$, unless otherwise specified.

Figure 1, Efficiency




Figure 2, Power dissipation





Figure 3, Input V-I, Iout=1A



Typical Waveforms

Conditions: TA = 25°C (77°F), Vin = 12V, unless otherwise specified

Figure 4, 25% - 50%load dynamic



Figure 5, 50% - 75%load dynamic





Figure 6, Output voltage established (Iout = 1A)



Figure 7, Output ripple & noise (Iout = 1A)



Feature Description


Remote On/Off (EN) (Optional)

Logic Enable	Low level (0-10Vdc)	High level (10-23Vdc)	Left open
positive logic	Off	On	Off


Input Undervoltage Protection

The converter will shut down after the input voltage drops below the under-voltage protection threshold for shutdown. The converter will start to work again after the input voltage reaches the input under voltage protection threshold for startup. For the Hysteresis, see the Protection characteristics.

Various circuits for driving the EN



Simple control



Transistor control

Output Overcurrent Protection

The converter equipped with current limiting circuitry can provide protection from an output overload or short circuit condition. If the output current exceeds the output overcurrent protection set point, the converter enters hiccup mode. When the fault condition is removed, the converter will automatically restart.

Wiring Instructions

The input and output of this product is terminals. The user should ensure that the input and output wires and terminals are connected reliably, and pay attention to the wire diameter to meet the requirements of the power supply current. If the cable to be used is long, it needs considering the voltage drop of the wire, if the voltage drop is too large, the voltage output at the load end may not meet the load demand. In this case, consider using a thicker wire diameter or reducing the length of the wire. Generally, if long wiring is required, long line should be used on the side where the current is relatively small. For example, this product is a step-down product, so long lines should be used on the input side.

Overtemperature Protection

A temperature sensor on the converter senses the average temperature of the module. It protects the converter from being damaged at high temperatures. When the temperature exceeds the over temperature protection threshold, the output will shut down. It will allow the converter to turn on again when the temperature of the sensed location falls by the value of Over temperature Protection Hysteresis.

Thermal Consideration

Sufficient airflow should be provided to help ensure reliable operating of the RW-968-12-24V-24W. Therefore, thermal components are mounted on the top surface of the RW-968-12-24V-24W to dissipate heat to the surrounding environment by conduction, convection, and radiation. Proper airflow can be verified by measuring the temperature at the middle of the base plate.

