

RW-935-36-48-12-120W

Input Voltage	Output voltage	Output current	Output Power	Efficiency	Dimension
30-60V	12V	10A	120W	94%	74*74*32mm



The RW-935-36-48-12-120W is a Non-isolated DC-DC converter that uses a synchronous rectification technology, and features high efficiency and power density. It has the dimensions of 74mm x 74mm x 32mm (2.91 in. x 2.91 in. x 1.26 in) and provides the rated output voltage of 12 V and the maximum output current of 10A.

Features

- Design meeting RoHS / CE
- High efficiency: 94% (@ 48Vin, 25°C)
- Import capacitors, high reliability
- Output transient absorption protection
- Support -40 °C environment
- 100% full load burn-in test
- Remote ON/OFF control(optional)
- Waterproof level IP68
- 3 month warranty
- Short circuitOver load, Low voltage protections

Applications

- Industrial
 - Alternative Energy
 - Golf Cart
 - Forklift
 - Electromotor
 - Telecommunications
 - Boat & Yacht
 - Medical
 - LED Marketplaces
- and so on

Model naming method

RW-935-36-48-12-120W

RW-935 : SKU NAME
36-48: Input voltage range
12 : Output voltage
120W : POWER

Datasheet

Parameter	Min	Typ	Max	Units	Remarks
Absolute maximum ratings					
Operating ambient temperature	-40	-	+50	°C	
Shell ambient temperature	-40	-	80	°C	
Storage temperature	-55	-	100	°C	
Operating humidity	5	-	95	%	Non-condensing
Atmospheric pressure	62	-	106	kpa	
Altitude	-	-	4000	m	
Cooling way	-	-	-		Natural cooling
Input characteristics					
Input voltage	30	48	60	V	
Max. input voltage	-	-	63	V	Continuous
Undervoltage shutdown	25.0	25.3	25.5	V	Automatic recovery
Undervoltage recovery	28.0	28.2	28.5	V	Automatic recovery
Max. input current	-	-	4.5	A	Vin =30V; Iout =10A
No load current	-	20	30	mA	Vin =48V
Positive electrode cable	18	-	-	AWG	If the wire length is greater than 50cm, it is recommended to use a thicker wire diameter.
Negative electrode cable	18	-	-	AWG	

Enable PIN cable	-	NA	-	AWG	If the unit with this function
Fuse	-	20	-	A	Input positive has built-in fuse
Output characteristics					
Efficiency	-	94	-	%	Vin =48V; Iout =10A
Output voltage	11.8	12.0	12.5	V	Vin =48V; Iout =10A
Regulator accuracy	-	±2	-	%	
Voltage regulation	-	±2	-	%	
Load Regulation	-	±3	-	%	
Overvoltage protection	-	NA	-	V	
Output current	0	-	10	A	
Overcurrent protection	12	17	22	A	Vin=48V
External capacitance	-	NA	-	µF	Don't need
Output ripple and noise	-	120	150	mVp-p	Vin =30-60V; Iout=10A, Oscilloscope bandwidth: 20 MHz
Output voltage risetime	-	80	130	µS	
Boot delay time	-	100	150	µS	
Out voltage overshoot	-	2	3	%	Vin =48V, 50%-75%Load step
Over temperature protection	-	NA	-	°C	

Short circuit protection	-	YES	-		Long-term (4 hours)short circuit is not damaged, Hiccup mode
Positive electrode cable	16	-	-	AWG	If the wire length is greater than 50cm, it is recommended to use a thicker wire diameter
Negative electrode cable	16	-	-		

Safety and EMC features




Anti-electric Strength	Input to Output	-	V	Leakage current ≤ 3.5mA, 1min, no breakdown, no arcing
	Input to Shell	≥500	V	
	Output to Shell	≥500	V	
Insulation resistance	Input to Output	≥10	MΩ	Test voltage = 500V
	Input to Shell			
	Output to Shell			

Other characteristics

Weight	≤ 290	g	
Package	white box		
MTBF	≥200,000	H	Vin= 48V; Iout= 10A
Switching frequency	230±10	KHz	





Characteristic Curves

Conditions: TA = 25°C (77°F), Vin = 24V, Vout = 12V, unless otherwise specified.

Figure 1, Efficiency

Figure 2, Power dissipation

Figure 3, Input V-I, Iout=10A


Typical Waveforms

Conditions: TA = 25°C (77°F), Vin = 48V, unless otherwise specified.

Figure 4, 25% - 50%load dynamic

Figure 5, 50% - 75%load dynamic

Figure 6, Output voltage established (Iout = 10A)

Figure 7, Output ripple& noise (Iout = 10A)


Feature Description


Remote On/Off (EN) (Optional)

Logic Enable	Low level (0-30Vdc)	High level (30-60Vdc)	Left open
positive logic	Off	On	Off


Input Undervoltage Protection

The converter will shut down after the input voltage drops below the under-voltage protection threshold for shutdown. The converter will start to work again after the input voltage reaches the input under voltage protection threshold for startup. For the Hysteresis, see the Protection characteristics

Various circuits for driving the EN



Simple control



Transistor control

Output Overcurrent Protection

The converter equipped with current limiting circuitry can provide protection from an output overloader or short circuit condition. If the output current exceeds the output overcurrent protection set point, the converter enters hiccup mode. When the fault condition is removed, the converter will automatically restart.

Wiring Instructions

The input and output of this product is terminals. The user should ensure that the input and output wires and terminals are connected reliably, and pay attention to the wire diameter to meet the requirements of the power supply current. If the cable to be used is long, it needs considering the voltage drop of the wire, if the voltage drop is too large, the voltage output at the load end may not meet the load demand. In this case, consider using a thicker wire diameter or reducing the length of the wire. Generally, if long wiring is required. Long line should be used on the side where the current is relatively small. For example, this product is a step-down product, so long lines should be used on the input side.

Thermal Consideration

Sufficient airflow should be provided to help ensure reliable operating of the RW-935-36-48-12-120W

Therefore, thermal components are mounted on the top surface of the RW-935-36-48-12-120W to dissipate heat to the surrounding environment by conduction, convection, and radiation. Proper airflow can be verified by measuring the temperature at the middle of the base plate.

