


Input voltage	Output voltage	Output current	Output power	Efficiency	Size
15-80V DC	12V DC	1A	12W	91%	65*25*20mm

The RW-1012-72V-12V-12W is a Non-isolated DC-DC converter that uses a synchronous rectification technology, and features high efficiency and power density. It has the dimensions of 65*25*20mm and provides the rated output voltage of 12V and the maximum output current of 1A



Features

- Designmeeting RoHS / CE
- High efficiency: 91% (@ 72Vin, 25°C)
- Input transient absorption protection
- Output transient absorption protection
- Support -40 °C environment
- 100% full load burn-in test
- 3 month warranty
- Remote ON/OFF control (optional)
- Waterproof level IP68

Applications

- Industrial
- Alternative Energy
- Golf Cart
- Forklift
- Electromotor
- Telecommunications
- Boat & Yacht
- Medical
- LED Marketplaces and so on.

Model naming method
RW-1012-72V-12V-12W

RW-1012: SKU NAME
72V: Input voltage
12V : Output voltage
12W: Output Power

Parameter	Min.	Typ	Max.	Units	Remarks
Absolute maximum ratings					
Operating ambient temperature	-40	-	+50	°C	
Shell ambient temperature	-40	-	80	°C	
Storage temperature	-55	-	100	°C	
Operating humidity	5	-	95	%	Non-condensing
Atmospheric pressure	62	-	106	Kpa	
Altitude	-	-	4000	m	
Cooling way	-	-	-		Natural cooling

Input characteristics

Input voltage	15	48/72	80	V	-
Max. input voltage	-	-	80	V	Continuous
No load current		0.1	0.12	W	Vin =72V

Output characteristics

Efficiency	-	91	-	%	Vin =72V; Iout =1A
Output voltage	11.8	12	12.2	V	Vin =72V; Iout =1A
Regulator accuracy	-	±1	-	%	
Voltage regulation	-	±1	-	%	
Load Regulation	-	±1	-	%	
Overvoltage protection	-	82	-	V	@25°C TVS clamp protection
Output current	0	-	1	A	
Overcurrent protection				A	
External capacitance	0	200	1000	μF	Don't need
Output ripple and noise	-	18	22	mVp-p	Vin =15-80V; Iout=1A Bandwidth: 20 MHz;
Output voltage rise time	-	120	150	mS	
Boot delay time	-	180	250	mS	
Out voltage overshoot	-	1	2	%	Vin=48V , 50%-75% Load step;
Over temperature protection	-	-	80	°C	Shell temperature, @ 80°C Restore working
Short circuit protection	-	-	-		Long-term (4 hours) short circuit is not damaged, Hiccup mode

Safety and EMC features


Anti-electric Strength	Input to Output		V	Leakage current ≤ 3.5mA, 1min, no breakdown, no arcing
	Input to Shell	≥500	V	
	Output to Shell	≥500	V	
Insulation resistance	Input to Output	≥50	MΩ	Test voltage = 500V
	Input to Shell			
	Output to Shell			

Other characteristics

Weight	≥50	g	
Package	Color box		
MTBF	≥200,000	H	Vin =72V; Iout =1A
Switching frequency	220±10	KHz	

Thermal Consideration

Sufficient airflow should be provided to help ensure reliable operating of the RW-1012-72V-12V-12W. Therefore, thermal components are mounted on the top surface of RW-1012-72V-12V-12W to dissipate heat to the surrounding environment by conduction, convection, and radiation. Proper airflow can be verified by measuring the temperature at the middle of the base plate.



NEWTECH ENTERPRISES reserves the ©copyright and right of final interpretation.